

### Description

Wall mounted triple distribution board system with front and two side mounted distribution boards. Boards can be isolated by either one, two or three incoming isolators or extension MCCBs. Metering compartments are offered as an optional extra.

### Specification

- Fully type tested conditional short circuit rating of 25kA to BS EN 61439-3
- High performance MCB 10kA BS EN 60898 15kA BS EN 60947-2 in B, C or D curve 1, 2, 3, 4 pole
- 250A busbar rating
- Isobar disconnection to BS EN 60947-3 ensuring unused outgoing ways are isolated
- Option of switching outgoing neutral on all boards using distributed neutral kit
- Terminal block for feeding up to 100A
- Range of incomers: switch disconnectors, residual current devices, terminal blocks, mccb
- Single pole RCBO for new or retrofit maintaining device density
- Full range of device accessories and auxiliaries
- Knockouts for cable gland and conduit mixed to suit the installation needs without loss of space
- Removable insulated pan assembly
- Fully shrouded neutral
- Split neutral bars
- Removable gland plates
- Optional metering, dual supply, surge protection and contactor on incoming
- Metered extension enclosures



| Dimensions (mm) |        |       |       |
|-----------------|--------|-------|-------|
| Type            | Height | Width | Depth |
| 3 x 8 Way TPN   | 538    | 750   | 470   |
| 3 x 12 Way TPN  | 700    | 750   | 470   |
| 3 x 16 Way TPN  | 808    | 750   | 470   |
| 3 x 24 Way TPN  | 1024   | 750   | 470   |

